

# DILOG



[www.dilog.se](http://www.dilog.se)

## Dilog DCT-280HD

- Supporting DVB-C and DVB-T2
- SD / HD support (MPEG4 AVC/H.264)
- User friendly Installation
- 1 Cryptoguard Smartcard-Reader
- USB PVR Function (with external HDD)
- Time Shift Mode (with external HDD)
- Event Timer by EPG
- High Definition Video output : HDMI
- S/PDIF Dolby (coaxial) Subtitle support : OSD & VBI insertion for TV
- 4-segment LED Display
- Channel sorting by FTA, CAS, Alphabetic order & Network
- EPG : Now and Next and 7 days EPG
- Variable Input Symbol Rate
- User selectable output resolution
- Multi language OSD
- Fast Channel Change
- Memory for up to 5,000 TV & Radio Channels
- PIG (Picture In Graphic)
- 8 Favorite List & Unlimited Programs per each
- Channel Edit Function
  - Move, Delete, Favorite Edit
  - Parental Lock, Channel Rename, Channel Skip
- Manual PID/ Satellite & TP/ Network Scan
- S/PDIF – coaxial (Digital Audio or Dolby AC3 stream out)
- Software Upgrade via OTC & USB

# Technical Specification



## A/V Rear Port

HDMI	1 (1.3)
RCA-Jack	Video, Audio L/R Output
Digital Audio (S/PDIF)	Coaxial
USB 2.0	1
RF Modulator	Optional

## Front Panel

Display	7-segment, ON/OFF LED
Front Panel Keys	Standby, CH+, CH-
Cardreader	1 Cryptoguard Smartcard Reader

## Memory and Chip

CPU	3812
DDR2	128MB
FLASH	8MB

## Physical Specification

Net Weight	1,2 kg
Dimensions (WxHxD)	195x40x145 mm
Operating Temperature	0~40°C

## Remote Control

Type	Infrared (Carrier Freq. 38kHz)
Qwerty Remote	2 x 1.5 V AAA

## Power Supply

Input Voltage	AC100-240V~, 50/60Hz,
---------------	-----------------------

## EAN

7 350 021 772 800

# DILOG

Dilog Nordic AB  
Faktorvägen 9, 434 37 Kungsbacka Sweden

Tel: +46 31 28 88 30  
Fax: +46 31 28 82 33  
www.dilog.se