

DILOG



www.dilog.se

Dilog DIP-701

- Digital IP-box med möjlighet till hårddiskinspelning via USB*
 - Inbyggd Cryptoguard
 - Klar för MPEG4/MPEG2 HD/SD sändningar
 - Elektronisk programguide
 - Digital optisk ljudutgång
 - HDMI
 - Videoformat 576i, 576p, 720p, 1080i.
- *Rekommenderade Hårddiskar Seagate Expansion portable STBX

Technical Specification

Video Decoding

Transport Stream Profile Level	MPEG-2 ISO/IEC 1318-1 MPEG-2 MP@ML, MPEG-2MP@HL, MPEG-4 AVC/H.264 HP@L4
Video Format	4:3, 16:9
Video System	PAL, NTSC
Video Resolution	1080p, 1080i, 720p, 480p, 480i

Audio Decoding

Audio Decoding	MPEG-1, Musicam Layers 1&2
Audio Mode	Single Channel, Dual Channel, Joint Stereo, Stereo
Sampling Rate	32, 44.1 & 48KHz

Chip & Memory

CPU	ST40 CPU core : 450MHz(STi7105)
Flash Memory	64Mbyte
SDRAM	DDR2 1Gbits x 2(256MB)
EEPROM	8Kbyte

Conditional Access Interface

CAS	CryptoGuard
Smart Card Reader	Side

A/V & Data In/Out

RCA A/V Component HDMI	Video output, Audio L/R YPbPr Digital Video and Audio output(HDMI / HDCP Certified by 1.4a) Fast Ethernet(10/100) Front side USB Ports 2.0 (Rear Panel side)
Ethernet IR receiver 1xUSB	

Power Supply

Input Voltage	Adaptor, DC12V 2.5A
Power Consumption	Max 12W (Standby : Less than 1W)

Front Panel

Display	1 LED (2 Color - Green : Operating, Red : Standby)
---------	---

Physical Specification

Net Weight	260g
Gross Weight	990g (including all accessories)
Dimensions (W*H*D)	180x33x132 mm
Operating Temperature	0~50°C
Storage Temperature	-10~+60°C
Gift Box Size (W*H*D)	282x58x199
Master pack Size (W*H*D)	428x322x320 (G/Box 10pcs)

EAN

7 350 021 777 010

DILOG

Dilog Nordic AB
Faktorvägen 9, 434 37 Kungälv Sweden

Tel: +46 31 28 88 30
Fax: +46 31 28 82 33
www.dilog.se